# The New Form Factor efus™

Our latest product family represents 20 years of experience in RISC Boards

easy	starter kits customized operating systems (Linux, WEC 2013) free support from F&S	Original Size
functional	various interfaces expandable with wireless modules easy base board based on "EasyLayout" standard	
universal	visualization communication control	Fillent (Chil
small	47 x 62mm only 5V Single Supply	

The **efus**<sup>™</sup> project guarantee stands for free support. We are always at your side during your development. To start your project optimally, we offer starter kits and workshops. The **efus**<sup>™</sup> A9 Computer-On-Module price (per 1000) also offers the lowest baseboard costs for YOUR development and production!

#### Why?

Our answer is **EASYMOUNT**! No need for screws to fix the module in high vibration surroundings, just click the module on your baseboard and the unit is resistant for shocks up to 50G!

**EASYLAYOUT**: Only 4 layers are needed to cause a minimum of crossing wires and a minimum count of vias for your baseboard. We developed our new form factor **efus**<sup>™</sup> with focus on minimizing your development time.



You can start directly - just in time – you only need to download the EAGLE Source board design and libraries! Just put your needs on the baseboard and place your prototype order!

You want to have a special custom chip ON MODULE?

We have the solution: We will develop a special interface opposite the LVDS connector.

We offer inexpensive expandable areas, so the custom chip (e.g. WLAN, ZigBee, etc.) can be placed on module – only the software drivers need to be adjusted.

Our customers trust us: more than 60 % of our generated revenues come from the medical device industry.



## efus™A9

with Freescale i.MX6 Cortex-A9 Single- and Dual-Core CPU



#### Description

The applied i.MX6 Cortex-A9 CPU comes with high performance, excellent multimedia features like 3D graphics (100MTri/s, 1000Mpx/s), Hardware Decoder/Encoder with a resolution up to 1080p, H.264 HP, HDMI v1.4., ARMv7™, NEON and VFPv3. Freescale's focus on chip design was low power consumption.

When using the ARM Cortex-A9 CPU, you definitely constitute the right compromise between performance/MHz and power consumption/MHz (0.35mW/MHz). ARM Cortex-A15 does indeed offer a higher performance (about 70% more at equal frequency), but it also has a much higher power consumption (about 100% more at equal frequency). Other important features are the long-time availability of up to 15 years and the temperature range of -40°C - +85°C.

Additionally, the module offers various interfaces. It also enables the possibility to control a RGB display, a LVDS display and a DVI screen simultaneously.

HDMI/DVI

### simultaneous displaying

#### Support

Linux, WEC 7, as well as Windows Compact 2013 are available for efus<sup>™</sup>A9. All starter kits are shipped with 7" TFT and pre-installed operating system. Optionally one has the opportunity to book a four-hour workshop in the short term (Windows Embedded CE or Linux). The customer can choose from additional hard- and software extensions (camera kit, Update program, safe file system, etc.).We are looking forward to your questions via forum, phone, e-mail or in person.



Technical Data			
Power Supply:	+5V <sub>DC</sub> / <u>+</u> 5%		
Power Consumption:	tbd		
Interfaces:	1x Ethernet 10/100/1000MB		
	4x Serial		
	1x USB2.0 Host		
	1x USB2.0 Device		
	2x CAN2.0		
	2x I <sup>2</sup> C		
	2x SPI		
	1x I2S (Audio Codec)		
	2x SDIO (SD-Card)		
	1x SATA		
	PCIe (2.0)		
	Camera Interface /YUV4:2:2 CCIR-656		
TFT LCD-Interface:	18bit RGB &		
IFI LCD-Intenace.	1-2x 24bit LVDS & DVI	je Je	
RAM:		r & Tr	
	up to 1GB DDR3-RAM	S. Pat	
Program Memory:	up to 1GB Flash + 32GB eMMC	notice t Corp eg. U.:	
Processor:	ARM Cortex-A9	hout i rosoft c., Re	
F1008501.	Single-/Dual-Core	ge wit of Mic tor, In	
	800MHz/1GHz	chan mark onduc	
Temperature Range:	0°C - +70°C ,	ect to tradel temico	
remperature range.	(-20°C - +85°C/	s subj tered cale S f ARN	
	-40°C - +85°C optional)	nenti regis Frees	
Size:	47mm x 62.1mm x 11mm	docur Hisa Irk of F	
	(I x b x d)	n this ded C dema	
Weight:	tbd	ation ii mbedi s a tra registe	
<b>U</b>		The information in this document is subject to change without notice. Windows Embedded CE is a registered trademark or Microsoft Corp. Freescale is a trademark of Freescale Semiconductor, Inc., Reg. U.S. Pat. & T.m. Off Corex is a registered trademark of ARM.	
		The information in this document is subj Windows Embedded CE is a registered I Freescale is a trademark of Freescale S Cortex is a registered trademark of ARM	

